



**VICTORIA UNIVERSITY**  
MELBOURNE AUSTRALIA

*A review on methods of finding losses and cooling methods to increase efficiency of electric machines*

This is the Published version of the following publication

Gundabattini, Edison, Kuppan, Ravi, Solomon, Darius Gnanaraj, Kalam, Akhtar, Kothari, DP and Abu Bakar, Rosli (2021) A review on methods of finding losses and cooling methods to increase efficiency of electric machines. Ain Shams Engineering Journal, 12 (1). pp. 497-505. ISSN 2090-4479


The publisher's official version can be found at  
<https://www.sciencedirect.com/science/article/pii/S2090447920301854>  
Note that access to this version may require subscription.

Downloaded from VU Research Repository <https://vuir.vu.edu.au/43035/>



Contents lists available at ScienceDirect

Ain Shams Engineering Journal

journal homepage: [www.sciencedirect.com](http://www.sciencedirect.com)

# A review on methods of finding losses and cooling methods to increase efficiency of electric machines

Edison Gundabattini<sup>a</sup>, Ravi Kuppan<sup>b</sup>, Darius Gnanaraj Solomon<sup>a,\*</sup>, Akhtar Kalam<sup>c</sup>, D.P. Kothari<sup>d</sup>, Rosli Abu Bakar<sup>e</sup>

<sup>a</sup>School of Mechanical Engineering, VIT, Vellore, India

<sup>b</sup>School of Electrical Engineering, VIT, Vellore, India

<sup>c</sup>Dept of Electrical and Electronics Engg., Victoria University of Technology, Melbourne, Australia

<sup>d</sup>Former Director, Indian Institute of Technology, Delhi, India

<sup>e</sup>Faculty of Mechanical Engineering, University Malaysia Pahang, Malaysia

## ARTICLE INFO

### Article history:

Received 29 July 2019

Revised 11 May 2020

Accepted 10 August 2020

Available online 2 October 2020

### Keywords:

Electric motor

Losses

Cooling

Efficiency

## ABSTRACT

Performance of electric motors and losses in terms of heat and temperature are reviewed in this paper. Airgap eccentricity, electromagnetic performance, effect of temperature and losses are shown as factors affecting the efficiency. Several methods of computer aided analyses are listed. Temperature distribution in an induction motor is shown through the results of a simulation. Different cooling methods are reviewed. Future directions for research include cryogenic cooling, heat pipes and usage of phase change materials.

© 2020 The Authors. Published by Elsevier B.V. on behalf of Faculty of Engineering, Ain Shams University. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

## 1. Introduction

Electric motors have been utilized since 1834, and they have played a vital role in our day to day lives. Today, they continue to replace diesel and gas engines, as well as hydraulic cylinders, while evolving into new designs optimized for EVs (electric vehicles) and other technologies. “Electric motors are being used more widely in ships, airplanes, trains, and cars. We’re also seeing a lot more electric motors in electric vehicles. “The ongoing transition from gas to electric is primarily driven by the need for more efficient devices that run with cleaner energy sources. Yet, electric motors also tend to be more responsive, and are more adaptable to new applications, especially in Electric truck. There is an increasing need to improve the fuel economy and reduce Green House Gas

(GHG) emissions of heavy duty trucks due to high fuel prices, regulatory pressures, and climate change. Three approaches can be used to improve the fuel economy and/or reduce GHG emissions of heavy-duty trucks: non-electrification efficiency-improving technologies on conventional powertrains and vehicles [1–3], hybrid powertrain technologies [3,4], and the substitution of natural gas, electricity or hydrogen for diesel fuel [5,6]. So far different types of motors have been used in electric truck. The main difference between electric propulsion on ships vs. cars is related to torque requirements, says Kirtley [7,8]. The variable speeds used in a car require that “the gearbox adapt the engine to the road, You can generate an electric motor that can propel an automobile without a gear shift. In the past, Kirtley has consulted with Tesla Motors on its electric cars, and both agree that “the induction motor” is the best for electric automobiles.

\* Corresponding author.

E-mail addresses: [edison.g@vit.ac.in](mailto:edison.g@vit.ac.in) (E. Gundabattini), [k.ravi@vit.ac.in](mailto:k.ravi@vit.ac.in) (R. Kuppan), [dariusgnanaraj.s@vit.ac.in](mailto:dariusgnanaraj.s@vit.ac.in) (D.G. Solomon), [akhtar.kalam@vu.edu.au](mailto:akhtar.kalam@vu.edu.au) (A. Kalam), [dpk0710@yahoo.com](mailto:dpk0710@yahoo.com) (D.P. Kothari), [rosli@ump.edu.my](mailto:rosli@ump.edu.my) (R. Abu Bakar).  
Peer review under responsibility of Ain Shams University.

## 2. Performance of electric motors

The types of high-speed machines include induction machines, permanent-magnet machines and switched reluctance machines. Electric motors have a very high efficiency and high-power density, hence they find a perfect application in vehicle traction. They are fit for the downsizing concept also because they can produce maximum torque at low rotational speed. In all the types of electric



Production and hosting by Elsevier

<https://doi.org/10.1016/j.asej.2020.08.014>

2090-4479/© 2020 The Authors. Published by Elsevier B.V. on behalf of Faculty of Engineering, Ain Shams University.

This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

machines, the squirrel-cage induction motor is the most opted one. A motor failure can result in the loss of large revenues, hence a thorough thermal analysis is done [9–11].

Electric motors and drive systems account for 64% of industrial electricity consumption. Energy which is not converted into useful work results in heating of the various motor components, and accounts for the motor losses. Heat generated during operation causes a negative effect on motor efficiency. The torque/rotational speed of the electric motor is being affected by temperature and internal losses viz. winding conduction losses, stator core losses, rotor core losses, and permanent magnet eddy current losses as well. To ensure a satisfactory life span for the motor, temperature rise must be limited to safe values. Obviously, the quantity of heat generated must be effectively removed to prevent damage to the machine using appropriate cooling methods [12–14].

Fig. 1 shows the contributors for developing high torque. Maximum torque can be obtained by the electric motor using power electronics, and high voltage battery, but increases the weight as well. In addition, although they have high efficiency, they produce a significant amount of heat that has to be removed. Much lower temperature can be accepted and higher values can request **power de-rating** in order to preserve their functionality. High voltage battery is even more critic, since it can work correctly only in a specific temperature window and outside this, it has a **rapid thermal degradation**. Maximum torque at different speeds possible for a specified winding and rotor temperature. Peak torque envelope for thermal transient condition can be calculated for a set amount of time that gives a certain maximum winding temperature [15].

2.1. Factors affecting the efficiency of electric motors

The calculation of losses in induction motors is particularly important, as it directly influences the temperature distribution, and also the overall motor efficiency. Predicting the temperature distribution is made difficult because of the uncertainties associ-

ated with assigning losses and thermal coefficients. These losses play an important role in determining the efficiency and temperature rise, and hence, the rating of a machine. The importance of **stray load losses** in induction machines was illustrated, indicating that a small improvement of the efficiency would mean about five times reduction in the losses of the input power. Hence, a small improvement of the average effective efficiency of the industrial motor would save energy [16,17]. Fig. 2 shows the factors affecting the motor efficiency.

2.1.1. Airgap eccentricity

One of the types of faults that can occur in Induction motors is **air gap eccentricity**. Static eccentricity is displacement of the rotation axis of the rotor with regard to the geometric center of the stator, hence the field distribution in the air-gap is unsymmetrical. The reasons for eccentricity include intrinsic shaft tolerance, ball-bearings defects or problems related with the fixing of these motor parts. This would cause the eccentricity to create additional motor vibrations and unbalanced magnetic pull (UMP). The static eccentricity leads to a non-uniform temperature distribution and the small eddy-current losses which occur in the magnets, contributes to the rise of the highest temperature spot in the motor, potentially shortening the lifespan of the **stator insulation system**. In Dynamic eccentricity the rotation axis of the rotor do not coincidence with its geometric center [11,18–22].

2.1.2. Electromagnetic performance

Mass, volume and material properties of electric motor have to be temperature-dependent so that temperatures inside the machine can work with a good **electromagnetic performance**. This analysis makes it easier for designers to maximize the winding current density to achieve the highest possible torque/power ratings within thermal limits set by the winding insulation or **demagnetization** limits [23,24]. The electrical machines in the automotive industry use permanent magnets in their rotors as they possess very good efficiency and high power density. On the other hand, sensitivity of the magnets in high temperatures is the major drawback. The losses caused by the eddy-currents induced in the rotor magnets are relatively small compared to the other losses generated in the electric machine. But due to the relatively poor




Fig. 1. Contributors for high torque.




Fig. 2. Factors affecting the motor efficiency.

heat dissipation of the rotor, these losses can cause significant heating of the magnets. Increased temperature in the magnets may result in partial irreversible **demagnetization** of them as shown in Fig. 3. Abnormal high temperature will also affect the **core resistivity, thus affecting the eddy current loss** [25].

### 2.1.3. Temperature rise and losses

Operating point of the permanent magnet is subjective to the exposed temperature. Hence, the distribution of the **magnetic field** inside the motor, the **magnetic flux density** in the **air gap** and the core will change. Changes in magnetic field will affect **iron losses** and **permanent magnet eddy current losses**. Rise in temperature may alter the thermal conductivity, the resistance of the copper core, the permanent magnet remanence and intrinsic coercivity.

In general the highest temperature appears in the winding copper core, and the lowest temperature appears in the housing as shown in Fig. 4. Because the winding copper core is the main heat source and the small heat dissipation factor of the insulation layer leads to poor heat dissipation, the peak value of the temperature is located at the center of the stator winding. The eddy current losses are regarded as heat sources. With the increase of the load, the temperatures of the housing, stator core, winding copper core increases non-linearly. As the main heat source, the copper core is located in the middle of the stator and surrounded by insulations. The temperature will sharply rise because of the eddy current loss in the permanent magnet and poor thermal conduction ability of the rotor [26].

Increase of the power density would allow the motor temperature rise in the range of allowable limit value. Reducing the temperature rise can happen by improving the cooling capacity of motor and by reducing the losses. With the high speed and large carrier frequency, the **eddy current loss** of the permanent magnet is large [27]. Heat generated by a running induction motor and the temperature raise, eventually leading to thermal stresses. If the thermal stress is more than the limiting stress of the structure of the cage, it may lead to **broken bar fault** and the **cage fracture in the joint of the bars and the rings**. This is a very serious accident as it would lead to asymmetric rotor operation. Temperature rise is a key performance parameter of concern in the industrial arena. The temperature rise can limit the rated power and reduce the motor efficiency, and it also imposes special demands on the material of the motor. Hence, thermal mapping is crucial for satisfying the requirements of functionality and safety [28].

The influence of the end of the stator and rotor on axial temperature distribution also contributes to thermal loss. The temperature of stator and rotor increase rapidly in the beginning and the rotor temperature is higher than the stator temperature all the time. The maximum temperature point is around the axial center of the rotor bar. The axial temperature difference of the rotor core




Fig. 3. Damages caused by temperature rise.




Fig. 4. Hottest spots in the motor.

is larger than that of the stator core while the radial temperature difference of the stator core is larger than that of the rotor core [18].

### 2.1.4. Power losses

Fixed losses are losses in the active iron, and additional no load losses in other metal parts, Losses due to friction and windage loss in the machine. Load losses are copper losses in primary windings, losses in secondary windings and additional load losses. Stator losses,

- Stator Copper losses: losses are produced when the current passing through the stator windings, and generates the heat and consequently, the temperature of the motor rises. These losses are dependent on the square of stator current.
- Rotor bars losses: losses are produced when the current passing through the rotor bars, they are dependent on the square of rotor current.
- Iron losses or core losses: losses are generated in the conducting core laminations, due to hysteresis, eddy-current. These play an important role in design of the machine and in determination of its thermal rating.
- Mechanical losses contain air friction losses and bearing friction losses. Air friction losses result following the air circulation around the rotor during its operation. The air friction losses are divided in to two parts: the losses corresponding to the rotor seen as a rotating cylinder and the losses corresponding to the end surfaces of the rotor. Bearing friction losses are the results of the relative motion in bearings.

Copper losses are due to Joule losses, iron losses are due to eddy current and hysteresis effect. Compared to the conventional engine losses, they are quite low because the power is generally lower and the efficiency is much higher. Electric motors have very high efficiency, however their power losses produce a significant amount of heat. All the power losses become heat and increase the temperature of the component. The maximum temperature have an important effect on the **de-rating** of the power electronic components. In order to avoid premature de-rating, it is important to

leave the temperature as low as possible [10]. **Core loss** seen in Fig. 5 is much greater than other losses and is the main source of heat due to the high operating frequency. Therefore, it is of crucial importance to calculate the core loss accurately, taking operating temperature into account. The **core eddy current loss and hysteresis loss** are due to temperature-induced changes in core material resistivity [9]. In order to design a high-efficiency motor, the iron loss generated in the motor should be reduced. The **stator loss, armature winding loss, rotor loss, and axial structure loss** are assigned as the heat sources in the electrical machine. The large rotor's **eddy current loss** will cause the temperature of permanent magnet to increase considerably [29–32].

2.1.5. Methods of reducing losses

A speed vector control system of induction motor (IM) with minimization of the copper and iron losses has been introduced. This method reduces heat losses from the rotor windings and stator and core losses from eddy currents [52]. Results of a sensitivity analysis of the heat sources and the properties of the structural changes within a 3D-model are presented. Iron losses and ohmic losses in copper are examined on the basis of electromagnetic design. The criteria for future design of electric motors are shown [53]. High temperature superconductor (HTS) machines have been designed to use an iron core to reduce the HTS tape length. Further study is required to find the arrangement of HTS tape in iron core to reduce losses [54]. A stator magnetic core from segments of amorphous steel is developed. Ducts inside the stator are used as cooling ducts. These arrangements promote the dissipation of heat from the stator and minimize temperature [55]. Three different types of tape-wound laminations were analysed viz. heat treated (HT), glued and heat treated (GHT) and conventional non-treated (NT). HT and GHT type laminations have lower iron losses than NT and conventional stacked laminations [56]. Lumped parameter thermal network (LPTN) was used to find the thermal performance. Optimization of the reduction in iron loss and copper loss, eddy current loss in permanent magnet was carried out considering harmonics to improve thermal performance [57]. Experiments were carried out using lamination sheets fabricated through different manufacturing processes: insulation, laser cutting, electrical discharge machining (EDM) and thermal treatment. The best manu-

facturing processes were found to be the bonding varnish insulation and EDM cutting. Second stress-relieving thermal treatment on CoFe alloy reduced iron loss by 28% [58]. Hybrid excited axial field flux-switching machine (HEAFFSM) with permanent magnets (PMs) and excitation windings in its stator is a novel hybrid excited flux-switching PM machine. Experimental results show that the minimum-copper-loss (MCL) strategy minimises the copper loss of the HEAFFSM drive system [59]. Another study focused on the core losses in the stator region of high-speed permanent magnet synchronous motors, magnetic field characteristics in the load region, and variations in iron losses caused by changes in these areas. It was demonstrated that the running status of high speed motors is closely related to the stator iron losses [60].

2.2. Temperature distribution in an induction motor

The temperature distribution in the induction motor is not uniform and there is a risk of local overheating. The **winding** is a main heat source and its insulation is thermally sensitive, so reducing the winding temperature rise is the key to the improvement of the reliability of the motor. Large end winding is required for high electrical loading and for the high torque density. The nature of the low speed, high torque application means that the losses in the machine are dominated by those from the winding [33,34]. Fig. 6 shows the temperature distributions inside an induction motor.

The maximum torque of a motor is directly proportional to the flux produced by the magnets. By keeping the working temperature of the magnets low, higher power density can be achieved [21]. Using cast copper instead of cast aluminum as rotor bars and end rings can reduce the temperature of rotor effectively [18]. The influence of temperature on the relative permeability of iron core material can be obtained. Thermoelectric materials allow converting a temperature gradient into electricity [35]. The material properties of the motor impose the temperature limit. The maximum limit of temperature is linked to silicon properties [10]. The thermal model explains the temperature distribution inside the induction motor, to give a precaution about problems which will occur during the operating conditions, like the **induction motor insulation**.

2.3. Computer aided analysis to find losses

Fig. 7 shows the computer aided analysis and modelling techniques used by different researchers during the past 10 years.




Fig. 5. Different type of losses acting as heat sources.




Fig. 6. Temperature distributions inside the induction motor [36].




Fig. 7. Computer aided analysis to find losses.

The following techniques were used: Thermography, Simulation using FEM, PDC & dielectric spectroscopy, Ansoft Maxwell software, dynamic E&S modelling, design optimization, CFD, Motor CAD Emag, ANSYS FLUENT, ANSYS-ICEM, FEA method, SOLIDWORKS, commercial software Motor-CAD, cell method (CM), modified CM thermal model, 3D motor model using the ANSYS software, 3D fluid motion analysis and software Dakota. Taguchi methods are utilized to optimize the models.

### 3. Cooling methods

Motor cooling depends on conduction of lamination stacks, slot windings and end windings. It also depends upon the performance of the cooling jacket [37]. In thermal model, directions of the heat flows in the induction motor are important.

1. heat flow from the rotor bars through the air gap towards the stator winding and then to the stator iron then finally to the ambient through the round frame by convection.
2. heat flow from the stator end-winding and the rotor bars sides towards the end-cap air by convection and then to the ambient through the side frame by convection.

#### 3.1. Cooling techniques for improving efficiency

Efficient cooling systems are essential to minimize the operating temperatures of the motor hot spots, and in particular of the copper windings. Thus, an accurate thermal modelling of the motor and of the coupled cooling system is important to optimize the thermal management of the engine. Water jacket cooling system removes more than 99.5% of the heat generated while the remaining portion is removed by natural convection [61]. By convection, heat is transferred from solid to either gas or liquid through the surface layer and can be either natural or forced convection [38]. The optimal flow rate for cooling is determined through an unsteady state analysis to predict according to the insulation grade

[39]. A liquid-cooling system is often adopted where a cooling fluid (usually a 50% mix of water and glycol) is pumped into the components to be cooled and in a liquid-air heat exchanger, forced air cooled by means of cooling fans [40]. Oil spraying technique is used to cool the magnets in a safe operating temperature, increase their performance and also reducing their manufacturing cost. The oil-spraying cooling system, was designed to spray oil on the inside of the rotor of the electrical machine. Due to the high rotational speed the oil forms a thin film that absorbs the heat generated by the magnets [21]. Water-ethylene glycol (WEG) circulated through three cooling channels within the cooling jacket [41]. The main technologies used in cooling electric motors include forced air cooling, direct water cooling, alternative cooling fluids, immersion cooling, heat pipes, phase change materials, vapour compression refrigeration, thermo electric cooling and Stirling cycle cooling. The novel cooling systems such as Malone refrigeration, pulse tube refrigeration, thermo ionic cooling, thermo acoustic refrigeration, magnetic refrigeration and ejector expansion refrigeration are still being studied or at research status [42]. Thermal diagnostics of motor windings, stator windings and temperature distribution inside the electric motors are presented [43–45]. Analysis of temperature rise, thermal losses and thermal performance are carried out in detail [46–48]. Forced convection on enhanced surfaces, different oil cooling systems and cooling of traction motors by combination of methods are reviewed [49–51]. Heat pipes are effectively used in thermal management of electric motors which simplify the system structure and save more space compared with the other methods [62]. Rotor is cooled using spiral stator water jacket that uses forced convection with water ethylene glycol mixture (50–50%) and oil spray cooling system. A new ventilation Cooling structure of the radial-axial mixed ventilation system is designed to safeguard the structure of the motor [63]. Temperature-rise rate of oil-cooled motor under rated working conditions viz. same electromagnetic structure, is slower than that of water-jacketed cooled motor and can work for longer periods. The oil-cooled method is one of the best methods to cool sta-




Fig. 8. Applied cooling methods.

tor and a direct oil-cooling method is proposed in the cooling the end winding with oil immersion [64]. Potting silicon gelatin is encapsulated in the gaps between the end windings and the casing to dissipate the heat generated in the end windings quickly and to enhance the utilization efficiency of the whole water channels [65,66]. In the recent research, the experimental results predict

higher cooling performance of electric motor with a refrigerant. Obtained rated torque with a refrigerant cooled motor is around 60% higher than that of water cooled motor [67]. Recently nanofluids are used as advance coolants in order to increase the heat transfer capability of the cooling system and to keep the temperature of the electric motor at operational level. A 4% of nanoparticle of

Aluminum-oxide with base fluid (pure water) increases the heat transfer capability of the cooling system up to 40% [68]. A very recent research is on introducing 3-dimensional heat pipes into the gap between the winding and the casing. Potting silicon gelatin is used to fix the heat pipes which also increase the contact area and the heat pipes with the combination of potting silicon gelatin can effectively improve the heat dissipation efficiency of the water-cooling. This technique is one of the best solution to solve the problem of high winding temperature [69]. A review on increasing efficiency of electric motors using cooling methods, lightweight materials and novel manufacturing processes is available [70]. Fig. 8 shows the applied cooling methods.

#### 4. Research gap and future directions for research

In this review it is observed that thermal mapping temperature at various parts of the motor is not very clear. All the researchers pointed out there is rise in temperature but quantitative analysis is missing. High Temperature Superconductor (HTS) technology has to be investigated to improve efficiency of motors. Further study is required to find the arrangement of HTS tape in iron core to reduce losses. Vector control system of electric motors can be explored to reduce losses. Secondly, various cooling methods are studied but comparison of results and quantitative analysis are not explicitly mentioned. Further research can be done in Cryogenic cooling method, Hydrogen cooling method and cooling using phase change materials (PCM)/Heat pipe. Experimental studies are to be done on the novel cooling systems such as Malone refrigeration, pulse tube refrigeration, thermo ionic cooling, thermo acoustic refrigeration, magnetic refrigeration and ejector expansion refrigeration. Even combinations of various cooling methods for the parts of the motor may be applied since the parts of the motor are not equally stressed thermally. Hence, by adopting appropriate cooling methods, the temperature in the motor can be controlled which will enhance torque and efficiency of the electric machines. Optimized thermal management is required to be studied to visualize the electromagnetic effects brought by geometric changes dictated by thermal considerations. The selection of Grade F insulation material has to be studied further to meet the requirements of the motor for short-term temperature rise. Also, Impacts of adding three different amount of nanoparticles in the base fluid has to be studied to predict the thermal performance of the cooling system. An optimized efficient electric motor is the need of the hour for high torque transport applications leading to the mitigation of the effects of climate change.

#### Declaration of Competing Interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

#### References

- [1] Miller P. Reducing heavy-duty long haul combination truck fuel consumption and CO<sub>2</sub> emissions. Boston: Northeast States Center for a Clean Air Future; 2009.
- [2] Bachman LJ, Bynum CL. Effects of single wide tires and trailer aerodynamics on fuel economy and NO<sub>x</sub> Emissions of class 8 line-haul tractor-trailers. 2005 SAE commercial vehicle engineering conference, Rosemont, 2005.
- [3] Zhao H, Burke A, Miller M. Analysis of class 8 truck technologies for their fuel savings and economics. *Transp Res Part D: Transp Environ* 2013;23:55–63.
- [4] Karbowski D, Delorme A, Rousseau A. Modeling the hybridization of a class 8 line-haul truck. In: SAE 2010 commercial vehicle engineering congress, Chicago. Technical Paper 2010-01-1931. doi: <https://doi.org/10.4271/2010-01-1931>.
- [5] Davis BA, Figliozzi MA. A methodology to evaluate the competitiveness of electric delivery trucks. *Transp Res Part E* 2013;49(2013):8–23.
- [6] NREL report. Advanced technology vehicle evaluation: advanced vehicle testing activity – Norcal prototype LNG truck fleet; 2004. <http://www.nrel.gov/docs/fy04osti/35427.pdf>.
- [7] Kirtley Jr. James L. Traction motor design considerations. [http://web.mit.edu/kirtley/www/doe\\_kirtley\\_may\\_2011.pdf](http://web.mit.edu/kirtley/www/doe_kirtley_may_2011.pdf).
- [8] Kirtley Jr JL, Schiferl RF, Peters DT, Brush Jr EF. The case for induction motors with die-cast copper rotors for high efficiency traction motors. Society of automotive engineers world congress, April 22, 2009, Detroit, 2009.
- [9] Hong Do-K Wan, Choi Jae-Hak, Kim Dong-Jun, Chun Yon-Do, Woo Byung-Chul, Koo Dae-Hyun. Development of high speed induction motor for spindle systems. *IEEE Trans Magn* 2013;49(7):4088–91.
- [10] Morini Lorenzo, Cavina Nicolò. Thermal management model for a plug-in hybrid electric vehicle-thesis. France: Anno Accademico, University; 2016.
- [11] Faiz J, Ebrahimi BM, Akin B, Am Toliyat H. Finite-element transient analysis of induction motors under mixed eccentricity fault. *IEEE Trans Magn* 2008;44(1):66–74.
- [12] Croitorescu Valerian, Anthonis Jan, Vasiliu Nicolae. Thermal modeling of an electric motor used on road vehicle powertrain. University POLITEHNICA of Bucharest, LMS International, Engineering Services; 2012.
- [13] Bousbaine Amar. An investigation into the thermal modelling of induction motors. Thesis submitted to the University of Sheffield for the degree of Doctor of Philosophy; 1993.
- [14] Zhou Kan. Computationally-efficient finite-element-based thermal and electromagnetic models of electric machines A dissertation submitted in partial fulfillment of the requirements for the degree of Doctor of Philosophy. University of Michigan; 2015.
- [15] Goss James. Multi-physics electric motor simulation workflow; Motor design software by Motor design engineers. In: CADFEM Ireland 13th October 2017, [www.motor-design.com](http://www.motor-design.com). Motor Design Limited; 2017.
- [16] Jimoh AA, Findlay RD, Poloujadoff M. Stray losses in induction machines: Part I, Definition, origin and measurement. *IEEE Trans Power Apparatus Syst* 1985;PAS-104(6):1500–5.
- [17] Benamrouche N, Haddad S, Bousbaine A, Low FW. Measurement of iron and stray load losses in induction motors using the temperature-time method. *Measurement* 1997;20(2):91–6. ISSN 0263-2241.
- [18] Tai Y, Liu Z. Analysis on three-dimensional transient temperature field of induction motor. *Electric power industry; Proceedings of the CSEE*, 2010. ISSN: 0258-8013.
- [19] Barbour A, Thomson WT. Finite element study of rotor slot designs with respect to current monitoring for detecting static air-gap eccentricity in squirrel-cage induction motors. Industry Applications Conference, 1997. Thirty-Second IAS Annual Meeting, IAS '97., Conference Record of the 1997 IEEE, vol. 1. p. 112–9.
- [20] Bannae Sharifian MB, Faiz Jawad, Ebrahim Bashir Mahdi. Analysis of induction motor static eccentricity using time stepping finite element. International conference on electrical machines, ICEM 2006, Conf. Publ. No. 289, 2006.
- [21] Frob Johan, Lykartsis Odyssefs. Advanced cooling of electric machine in a hybrid vehicle application. Master of Science Thesis, Division of Electric Power Engineering, Department of Energy and Environment, Chalmers University of Technology, Goteborg, Sweden 2014, Report No. 1; 2014.
- [22] Nandi S, Ilamparithi TC, Lee Sang Bin, Hyun Doosoo. Detection of eccentricity faults in induction machines based on nameplate parameters. *IEEE Trans Ind Electron* 2011;58(5):1673–83.
- [23] Jiang W, Jahns TM. Coupled electromagnetic-thermal analysis of electric machines including transient operation based on finite element techniques. In: IEEE energy conversion congress and exposition, Denver, CO, 2013. p. 4356–63.
- [24] Prabhu, Chandrasekar V, Karthikeyan P, Lenin NC, Arumugam R. Vibration and thermal analysis of switched reluctance hub motor. *Eur J Sci Res* 2012;68(1):12–20.
- [25] Yanan Yu, Liang Deliang, Liang Zhe, Ze Qiji. Calculation for stator loss of high-speed permanent magnet synchronous machine in torque-speed envelope and restraint approach for circulating current in windings. *CES Trans Electr Mach Syst* 2018;2(2).
- [26] Si Jikai, Zhao Suzhen, HaichaoFeng Yihua Hu, Cao Wenping. Analysis of temperature field for a surface-mounted and interior permanent magnet synchronous motor adopting magnetic-thermal coupling method. *CES Trans Electr Mach Syst* 2018;2(1).
- [27] Li Bing, Li Ming. Calculation and analysis of permanent magnet eddy current, loss fault with magnet segmentation. *Math Problems Eng* 2016;2016.
- [28] Xie Ying, Guo Jinpeng, Chen Peng, Li Zhiwei. Coupled fluid-thermal analysis for induction motors with broken bars operating under the rated load. *Energies* 2018;11(8):2024.
- [29] Huang Yunkai, Hu Qiansheng, Zhu Jianguo. Magneto-thermal analysis of a high-speed claw pole motor considering rotational core loss. *Trans China Electro Tech Soc* 2010;25(5).
- [30] Sato Takeru, Enokizono Masato. Evaluation of stator core loss of high speed motor by using thermography camera. Department of Electrical and Electronic Engineering, Oita University, Oita 870-1192, Japan. Vector Magnetic Characteristic Technical Laboratory, USA, Oita 879-0442; 2017.
- [31] Li Dong, Wen Yinghong, Li Weili, Feng Bo, Cao Junci. Three-dimensional temperature field calculation and analysis of an axial-radial flux-type permanent magnet synchronous motor. *Energies* 2018;11. paper no. 1208.
- [32] Kou BQ, Cao HC, Li WL. Analysis of Losses in high speed slot less PM synchronous motor integrated the added leakage inductance. *Energies, Proc of*

- 2015 Intl conference on power electronics and energy engineering (PEEE 2015-1), 2015.
- [33] Godbehere J, Wrobel R, Drury D, Mellor PH. Experimentally calibrated thermal stator modeling of AC machines for short-duty transient operation. *IEEE Trans Ind Appl* 2017;53(4):3457–66.
- [34] Li Quanwu, Dou Manfeng, Tan Bo, Zhang Haitao, Zhao Dongdong. Electromagnetic-thermal integrated design optimization for hypersonic vehicle short-time duty PM brushless DC motor. *Int J Aerosp Eng* 2016;2016. Article ID 9725416.
- [35] Chahine Khaled, Ramadan Mohamad, Merhi Zaher, Jaber Hadi, Khaled Mahmoud. Parametric analysis of temperature gradient across thermoelectric power generators. *J Electr Syst* 2016;12(3):623–32.
- [36] Xia Y, Han Y, Xu Y, Ai M. Analyzing temperature rise and fluid flow of high-power-density and high-voltage induction motor in the starting process. *IEEE Access* 2019;7:35588–95.
- [37] Bennion Kevin. Thermal management enables more efficient and cost-effective motors. National Renewable Energy Laboratory, 2016 Annual Merit Review; 2016.
- [38] Huai Ying, Melnik Roderick VN. Computational analysis of temperature rise phenomena in electric induction motors. *Appl Therm Eng* 2003;23(7):779–95.
- [39] Lee Jun Ho, Lee Gee Soo, Yu Byung Hun, Kim Hyun Chul, Kim Kyu Sik, Lee Bong Hyun. Design and thermal analysis of wheel hub motors of electric vehicles using analytical and CFD methods. International electric vehicle symposium and exhibition (EVS28), KINTEX, Korea, May 3–6, 2015, 2015.
- [40] Mapelli Ferdinando Luigi, Tarsitano Davide. Modelling of full electric and hybrid electric vehicles, new generation of electric vehicles. INTECH open science/open minds, New Generation of Electric Vehicles <https://doi.org/10.5772/45641>. Milan (Italy): Mechanical Department, Politecnico di Milano; 2012.
- [41] Bennion Kevin. Electric motor thermal management R&D. Annual report. National Renewable Energy Laboratory, U.S. Department of Energy; 2016. [www.nrel.gov/publications](http://www.nrel.gov/publications).
- [42] Rajapakse Prathibha Chinthana. Heat storage application in electric motor cooling system smoke ventilation motors. Master's Thesis in Sustainable Energy Engineering, Sweden: KTH Industrial Engineering and Management, University of Gavle; 2004.
- [43] Barański Marcin, Polak Artur, Komel Bobrme. Thermal diagnostic in electrical machines. *Electr Rev*; 2011. ISSN 0033-2097, R. 87 NR 10.
- [44] Baptista Bruno, Mendes André, Cruz Sérgio, Cardoso António. Temperature distribution inside a three-phase induction motor running with eccentric air gap. *Electr Rev* 2012. ISSN 0033-2097.
- [45] Stone GC. Power, condition monitoring and diagnostics of motor and stator windings – A review. *IEEE Trans Dielectr Electr Insul* 2013;20:No. 6.
- [46] Chen Qiping, Yang Xuelan. Calculation analysis of thermal loss and temperature field of in-wheel motor in micro-electric vehicle. *J Mech Sci Technol* 2014;28(8):3189–95.
- [47] Xia Yunyan, Han Yongsun, Xu Yongming, Ai Mengmeng. Analyzing temperature rise and fluid flow of high-power-density and high-voltage induction motor in the starting process. *IEEE Access* 2019.
- [48] Badran Omar, Sarhan Hussein, Alomour B. Thermal performance analysis of induction motor. *Int J Heat Technol* 2012;30:75–88.
- [49] Almaghrabi Mohammed. Forced convection cooling of electric motors using enhanced surfaces. Electronic Theses and Dissertations, Masters Thesis (Open Access), 5272, University of Central Florida; 2016.
- [50] Davin Tanguy, Pelle Julien, Harmand Souad, Yu Robert. Experimental study of oil cooling systems for electric motors. *Appl Therm Eng* 2015;75:1–13.
- [51] Gai Yaohui, Kimiabeigi Mohammad, Chong Yew Chuan, Widmer James D, Deng Xu, Popescu Mircea, Goss James, Staton Dave, Steven Andrew. Cooling of automotive traction motors: schemes, examples and computation methods– A review. *IEEE Trans Ind Electron* 2018.
- [52] Tolochko Olga, Kaluhin Dany Lo, Burmelov Oleksii. speed vector control of induction motor with copper and iron losses minimization. In: *EEE 2nd Ukraine conference on Electrical and Computer Engineering*, Lviv, Ukraine; 2019. p. 408–13.
- [53] Beck Christopher, Keller Daniel, Echtle Harald, Haug Sebastian, Kruger Christian, Bargende Michael. Sensitivity study on heat source distribution and heat transport of electrical machines. *E & I Electrotechnik und Informationstechnik* 2019;136:195–201.
- [54] Ogawa Jun, Fukui Satoshi, Oka Tetsuo, Sato Takao, Fushimi Atsumu, Shoda Takuya. Influence of the arrangement of HTS tapes inserted in an iron core on AC loss characteristics. *IEEE Trans Appl Conduct* 2014;24(3):6600204.
- [55] Ismagilov Flur R, Vyacheslav E, Vavilov Ruslan D. Karimov. Improving the efficiency of electrical high-rpm generators with permanent magnets and tooth winding. *Progr Electromagn Res M* 2018;63:93–105.
- [56] Syed Qurban Ali Shah, Solovieva Veronika, Hahn Ingo. Magnetization characteristics and loss measurements of the axial flux permanent magnet motor's stator. In: *IEEE international conference on electric machines and drives (IEMDC)*; 2019. p. 1061–6.
- [57] Seo Myung-Ki, Ko Young-Yoon, Lee Tae-Yong, Kim Yong-Jae, Jung Sang-Yong. Loss reduction optimization for heat capacity improvement in interior permanent magnet synchronous machine. *IEEE Trans Magn* 2018;54(11):8207705.
- [58] Boubaker Nadhem, Matt Daniel, Enrici Philippe, Nierlich Florent, Durand Guillaume. CoFe and SiFe lamination sheets and stemmed from different manufacturing processes. *IEEE Trans Magn* 2019;55(1):8100309.
- [59] Zhao Jilong, Lin Mingyao, Da Xu. Minimum-copper-loss control of hybrid excited axial field flux-switching machine. *IET Electr Power Appl* 2016;10(2):82–90.
- [60] Tao Dajun, Zhou Kai Liang, Lv Fei, Dou Qingpeng, Jianxiao Wu, Sun Yutian, Zou Jibin. Magnetic field characteristics and stator core losses of high-speed permanent magnet synchronous motors. *Energies* 2020;13:535. doi: <https://doi.org/10.3390/en13030535>.
- [61] Cavazzuti Marco, Gaspari Gloria, Pasquale Stefano, Stalio Enrico. Thermal management of a Formula E electric motor: Analysis and optimization. *Appl Therm Eng* 2019;2019:157. doi: <https://doi.org/10.1016/j.applthermaleng.2019.113733>.
- [62] Fang Guoyun, Yuan Wei, Yan Zhiguo, Sun Yalong. Yong Tang (2019) Thermal management integrated with three-dimensional heat pipes for air-cooled permanent magnet synchronous motor. *Appl Therm Eng* 2019;152:594–604. doi: <https://doi.org/10.1016/j.applthermaleng.2019.02.120>.
- [63] Zhu Gaojia, Zhu Yinghao, WenmingTong Xueyan Han, Zhu Jianguo. Double-circulatory thermal analyses of a water-cooled permanent magnet motor based on a modified model. *IEEE Trans Magn* 2018;2018:54. doi: <https://doi.org/10.1109/TMAG.2017.2759805>.
- [64] Guo Fulai, Zhang Chengning. Oil-cooling method of the permanent magnet synchronous motor for electric vehicle. *Energies* 2019;14:1–11. doi: <https://doi.org/10.3390/en12152984>.
- [65] Sun Yalong, Zhang Shiwei, Yuan Wei, Tang Yong, Li Jingrong, Tang Kairul. Applicability study of the potting material based thermal management strategy for permanent magnet synchronous motors. *Appl Therm Eng* 2019;149:1370–8. doi: <https://doi.org/10.1016/j.applthermaleng.2018.12.141>.
- [66] Patrick McCluskey F, Yonatan Saadon, Zhaoxi Yao, Alexander Camacho. Cooling for electric aircraft motors. In: *Intersoc. Conf. Therm. Thermomechanical Phenom. Electron. Syst. IThERM*, vol. 2019–May, 2019, p. 1134–8. <https://doi.org/10.1109/ITHERM.2019.8757435>.
- [67] Hidemasa Fujita H, Itoh Atshushi, Urano Tohru. Newly developed motor cooling method using refrigerant. *World Electr Veh J* 2019;2019:10. doi: <https://doi.org/10.3390/wevj10020038>.
- [68] Deriszadeh Ali, de Monte Filippo. On heat transfer performance of cooling systems using nanofluid for electric motor applications. *Entropy* 2020;22:99. doi: <https://doi.org/10.3390/e22010099>.
- [69] Sun Yalong, Zhang Shiwei, Chen Gong, Tang Yong, Liang Fuye. Experimental and numerical investigation on a novel heat pipe based cooling strategy for permanent magnet synchronous motors. *Appl Therm Eng* 2020;2020:170. doi: <https://doi.org/10.1016/j.applthermaleng.2020.114970>.
- [70] Solomon Darius Gnanaraj, Greco Adriana, Masselli Claudia, Gundabattini Edison, Rassiah Raja Singh, Kuppan Ravi. A review on methods to reduce weight and to increase efficiency of electric motors using lightweight materials, novel manufacturing processes, magnetic materials and cooling methods. *Annals de Chimie – Science des Materiaux* 2020;44(1):1–14.



**Prof. Edison Gundabattini** is working as a Professor in the Department of Thermal and Energy Engineering, School of Mechanical Engineering, Vellore Institute of Technology, Vellore, India. His research areas include: Renewable Energy, Wind energy and thermal mapping of mechanical and electrical systems



**Prof. Ravi K** is working as an Associate Professor in the Department of Electrical Engineering of the School of Electrical Engineering, Vellore Institute of Technology, Vellore, India. His research areas include: Power systems, Optimal power flow and electrical machines for electrical vehicles.



**Prof. Darius Gnanaraj S** is working as a Professor in the Design and Automation Department of the School of Mechanical Engineering, Vellore Institute of Technology, Vellore India. His research areas include: Materials, Ergonomics, Light weight motors for electrical vehicles.



**Dwarkadas Pralhaddas Kothari** is an educationist and professor who has held leadership positions at engineering institutions in India including [IIT Delhi](#), [Visvesvaraya National Institute of Technology, Nagpur](#) and [VIT University, Vellore](#), India. Currently, he is the Dean (R & D), J.D. College of Engineering & Management, Nagpur and earlier was Director General of Vindhya Institute of Technology and Science (VITS), Indore. As recognition of his contributions to engineering education, he was honoured as an [IEEE Fellow](#). His areas of research include: Power quality and modern power system analysis.



**Prof. Akhtar Kalam** is the Discipline Leader in Victoria University, Melbourne, Australia. His major areas of interests are power system analysis, communication, control, protection and cogeneration systems. He regularly offers professional development courses on Power System Protection, Renewable Energy and Cogeneration & Gas Turbine Operations.



**Prof. Dato' Ts. Dr. Hj. Rosli bin Abu Bakar** is working as a Professor in University Malaysia Pahang. His areas of research include: Energy, Electrical machines, Automobile Engineering and Renewable energy.